

Pytes

V5°



Features



Remote Monitoring and Upgrading



Higher Charge/ Discharge Rate



Wider Operation Temperature



Higher Energy Density



Greater Scalability

Inverter Compatibility List

Main Inverter Partner



V5° Specifications



Electrical

Nominal Voltage	51.2V
Voltage Range	47.5V~57.6V
Nominal Capacity	100Ah
Nominal Energy	5.12kWh
Recommended Charge/ Discharge Current ^[1]	75A(3.84kW DC)
Max Charge/ Discharge Current ^[2]	100A(5.12kW DC)
Peak Charge/Discharge Current	101A~120A(3min);121A~180A(15sec)

[1], [2]: The recommended and maximum charge/discharge currents apply when battery cell temperature is within 50°F ~ 104°F/10°C~40°C.
De-rated charge/discharge currents will occur if battery is operated outside of this temperature range.

General

Chemistry	LFP
Communication Protocol	CAN/RS485
Dimensions (L*W*H)	17.40*20.87*5.51 inch(3.2U)/ 424*530*140mm(3.2U)
Weight	97lbs/44kg
Operating Temperature	Charge:32°F~113°F/0°C~45°C Discharge:14°F~122°F/-10°C~50°C
Round-Trip Efficiency	≥95%
Cycle Life ^[3]	≥6000 cycles
Altitude	<13123.35ft/4000m
Warranty	10 years
Scalability	16 pcs (81.92kWh) in a group 6 groups (491.52kWh) in a system w/ a Hub

[3]: Test conditions 0.2C Charging/Discharging, @77 F/25 °C, 90% DOD

Special Features

WiFi Connection (Optional)	Remote monitoring and upgrade
Heating Pad (Integrated)	Temperature Rise:18°F/h/10°C/h Operation Temperature: -4°F~50°F/ -20°C~10°C

Certifications

UL9540 Ed.2 (2020), UL9540A, UL1973, CEC, SGIP

V5° Enclosures



Brackets for V5°
hold up to 1*V5°, stack up to 6*V5°



V-BOX-OC
hold up to 4*V5°



V-Box-IC
hold up to 3*V5°, stack up to 6*V5°



V-Box-NEMA 3
hold up to 2*V5°



V-Box-IC se
hold up to 3*V5°, stack up to 6*V5°

Case Study



Pytes

PYTES (USA) ENERGY, INC

Address: 13921 Senlac Dr, Farmers Branch, TX 75234
Site: www.pytesusa.com
Email: pytesusa@pytesgroup.com



LinkedIn



Facebook



YouTube



www.pytesusa.com

Pytes